

Product Specifications for the Spinner



FEATURES

- Capacity: 1,500 lbs
- Unique Patent Pending design
- No rollers
- Most aesthetic PWL on the market
- Rotates 180 degrees over dock for storage
- No pinch points (No exposed cables or rollers)
- · Winch positioned behind mast away from craft
- Comes with standard grab rail
- Smooth operation
- All marine grade aluminum
- 7 ½ ' vertical travel
- Five-year structural warranty
- Five-year gear box warranty
- Two-year motor warranty
- One-year comprehensive warranty

OPTIONS AND ACCESSORIES

- Remote control
- For additional options and accessories, please visit our web site at www.hi-tide.com.

PAGE 2

SPECIFICATIONS FOR THE SPINNER

All specifications subject to change without notice.

STRUCTURAL SPECIFICATIONS FOR THE HI-TIDE SPINNER											
MOTOR	VOLTAGE & AMPERAGE	CABLE SIZE & LENGTH	<u>MAST SIZE</u> CRADLE SIZE	MAX. BEAM MAX. LENGTH	CARPETED BUNKS	GRAB RAIL	PILE SIZE				
1/2 HP	120V/20A 240V/15A	1/4" x 30'	<u>5" x 5" x 12'</u> 4' X 5'	<u>6'</u> 16'	2" x 6" x 8'	2" x 36" x 46" Bent	8" or 10"				

WIRE SPECIFICATIONS FOR THE SPINNER												
MOTOR HP	100'		200'		300'		400'					
	120V	240V	120V	240V	120V	240V	120V	240V				
(1) 1/2	#12	#12	#10	#12	#8	#12	#6	#12				

RECOMMENDED PILING HEIGHT FOR THE SPINNER

